

Public Information

FLOODING - SEPTIC SYSTEMS

Homeowners, renters, and individuals staying in homes with septic systems should remember several things once floodwaters recede:

- Do not drink well water until it is tested.
- If possible, do not use the system if the soil is saturated and flooded. Flooded septic systems do not treat the wastewater, and untreated wastewater becomes pollution. Conserve water while the system restores itself and the water table falls.
- Have your septic tank professionally inspected and serviced if you suspect damage. Signs of damage include settling or an inability to accept water. Since most septic tanks are below ground and completely covered, they are not damaged by flooding. However, septic tanks and pump chambers must be professionally cleaned since they can fill with silt and debris. If silt clogs the soil absorption field, a new septic system may have to be installed.
- If sewage has backed up into the basement, clean the area and disinfect the floor.
 Use a chlorine solution of a half cup of chlorine bleach to each gallon of water to
 disinfect the area thoroughly. Wear rubber gloves and rubber boots. Avoid skin
 contact with floodwaters and the areas contaminated by them.
- Pump the septic system as soon as possible after the flood. Be sure to pump both
 the tank and lift station to remove silt and debris that may have washed into the
 system. Do not pump the tank during flooded or saturated drain field conditions.
 Pumping the tank is only a temporary solution. Under worst conditions, pumping it
 out could cause the tank to try to float out of the ground, damaging the inlet and
 outlet pipes.
- Do not compact the soil over the soil absorption field by driving or operating
 equipment. Saturated soil is especially susceptible to compaction. Compaction
 reduces the soil absorption field's ability to treat wastewater, leading to system failure.
- Examine all electrical connections for damage before restoring electricity.
- Be sure the septic tank's manhole cover is secure and that inspection ports are not blocked or damaged.
- Check the vegetation over your septic tank and soil absorption field. Repair erosion damage. Sod or reseed areas as necessary to provide turf grass cover.

Resources

"Environmental Protection Agency's Fact Sheets for "Emergency Disinfection of Drinking Water and What to Do After the Flood," August 2006.